

Rubiomonocoat REFRESH

DESCRIPTION:

Rubio Monocoat Refresh is a ready-to-use spray that refreshes, restores and protects surfaces treated with **Rubio Monocoat Oil Plus**. **Rubio Monocoat Refresh** is used when the surface feels too dry or rough, or when the finish has worn off due to heavy traffic. When the colour of the surface needs to be restored, we recommend a treatment with **Rubio Monocoat Maintenance Oil**, using the corresponding colour of the treated surface. **Rubio Monocoat Refresh** is just as effective when used on other oiled or varnished surfaces.

INSTRUCTIONS:

1. Eliminate dirt and dust from the floor.
2. Spray **Rubio Monocoat Refresh** on to the surface to be treated, or apply the product with a cloth. Use a minimal amount of the product to prevent the floor from becoming sticky.
3. Allow the product to react for a couple of minutes.
4. Wipe dry with a cloth, paper towel, or polishing machine with white pad. Finish the treatment using an absorbing cloth, until the surface feels completely dry.
5. Pay attention to handle medium sized zones that can be fully wiped dry within 15 to 20 minutes.
6. The surface can be walked on after 4 to 6 hours.

COVERAGE:

1 l = +/- 100 m2.

These usages are merely indicative. It is always recommended to make a sample in order to calculate the exact usage.

TECHNICAL SPECIFICATIONS:

Oil
 Unit weight: +/- 0,90
 Colour: opaque
 Odour: specific

STORAGE:

The product can be stored for up to 12 months.
 Store in dry conditions and in the original packaging.

PACKAGING:

Available in a 400 ml spray bottle – 0,5 l and 1 l can.

CAUTION:

The product may NOT be diluted!
Cloths, saturated with oil, may spontaneously combust.
After usage, they need to be soaked in water before disposal.

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.
 Date TDS: 30/08/10.



MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
 Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
 Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
 info@muyllefacon.be - www.rubiomonocoat.com

