

Rubiomonocoat CLEANER

RAW WOOD CLEANER.

DESCRIPTION:

Rubio Monocoat Cleaner is used as a cleaner for raw wood surfaces before the application of **Rubio Monocoat Oil Plus**. Also used to clean the materials that were used during the application.

Why use a small amount of **Rubio Monocoat Cleaner**?

- The revolutionary technology of **Rubio Monocoat Oil Plus** uses molecular reactions to ensure that the oil bonds with the wood fibres within 15 seconds. If there is dust on the surface, the oil will bond with the dust. As a result, when spreading the oil with the white pad, a microscopic paste will form on the surface.

The oil will have bonded with the dust instead of with the wood fibres.

- The cloth should only be slightly dampened with **Rubio Monocoat Cleaner**. In that way the dust will be collected electrostatically.

INSTRUCTIONS:

1. Sand and vacuum the surface in the appropriate manner.
2. Clean the surface with **Rubio Monocoat Cleaner**.
3. Allow the wood to dry till it regains its original aspect. Drying time: 15 minutes to 1 hour, depending on the degree of product that has been used to wet the surface.

TECHNICAL CHARACTERISTICS:

Physical state at 20 °C: liquid.

Colour: clear.

Final boiling point [°C]: 213 °C

Density [kg/m³]: 0,7 (15 °C)

Viscosity: 1,67 mm²/s (25°C)

Solubility in water: < 0,10 %

Flash point [°C]: > 62 °C

STORAGE:

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging.

PACKAGING:

1 L - 5 L can.

CONSUMPTION:

1 liter = +/- 75-100m².

These usages are merely indicative. It is always recommended to make a sample in order to calculate the exact usage.

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.

Date TDS: 30/08/10.

MUYLLE  **FACON**

MADE IN BELGIUM by **N.V. MUYLLE - FACON S.A.**
 Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
 Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
 info@muyllefacon.be - www.rubiomonocoat.com

