

Rubiomonocoat EXTERIOR WOOD CLEANER

DESCRIPTION:

Rubio Monocoat Exterior Wood Cleaner is used to clean wooden decks, fences, outside doors, carports and so forth. Removes grey discolouration, mildew stains and dirt.

DIRECTIONS FOR USE:

1. Dampen the surface with water. Use a hose - no high pressure cleaner.
2. Apply the ready-to-use **Rubio Monocoat Exterior Wood Cleaner** using a wide brush or similar.
For light cleaning, the product can be diluted with water at a ratio of 1:2.
3. Scrub the treated area with a scrubbing brush working length-wise along the wood until it is clean. You can also use a wood boy with black pad.
For stubborn stains, repeat the treatment.
4. Rinse thoroughly with water until all the foam has disappeared.
5. Allow the surface to dry completely.
6. Treat with the **Rubio Monocoat Exterior** wood protection product of your choice.

Do not use this product on padouk.

Important: RMC Exterior Wood Cleaner + Decking Oil Duo System

A good preparation is crucial in order to give an optimal guarantee on the system for years to come. All new, greying and previously treated wood should be treated beforehand with RMC Exterior Wood Cleaner.

Advantages:

- New wood > grease that appears naturally in some types of wood is removed.
 - > the natural pigmentation is washed out and as a result the colours of the primer will be more stable afterwards.
 - > the pores are opened, whereby the action of the nano pigments of our primer can be guaranteed in a better way, and the result will be smoother.
- Already treated and greying wood > the application will degrease and degrey the wood. Hereby you always start with a smooth colour, resulting in more control over the final result.

USAGE:

Brush: +/- 10 m²/l.

Woodboy & black pad: +/- 20m²/l

These usages are merely indicative. It is always recommended to make a sample in order to calculate the exact usage.

REFUSE:

Dispose of empty containers and waste in accordance with local regulations.

STORAGE:

The product can be stored for up to 12 months in a dry place and in the original packaging. Do not allow to freeze.

PACKAGING:

1L – 5L can.

UW VERDELER:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. MUYLLE FACON NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.
Date TDS: 30/08/10.

MUYLLE FACON

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiomonocoat.com

