

Rubiomonocoat PRECOLOR AQUA

DESCRIPTION:

RMC Precolor Aqua is a pre-coloring that allows to create contrast effects, applied in combination with a RMC Oil product. The the best possible molecular binding between the RMC Oil and the wood remains guaranteed. This combination technique creates unlimited creative possibilities, because all the colors of the Aqua palette can also be mixed with each other. (Do not mix with RMC Precolor Black.)

INSTRUCTIONS:

1. Sand the surface according to professional standards.
When renovating old floors, you must remove all the residues from previous treatments completely (varnish, oil, wax, etc.).
2. Vacuum the surface and clean with RMC Cleaner.
3. Stir the product well using a stirring rod.
Apply the RMC Precolor Aqua evenly, preferably with a special RMC brush on a stick or otherwise with a cloth or brush;
Watch out for overlapping: to avoid this, always finish an entire board of wood.
4. Allow the surface to dry for 1 to 3 hours. Drying times depend on the foundation, moistening, temperature and ventilation.

If any wood fibers are still upright, you will need to grind these using a floor polisher equipped with a beige-colored pad.
Afterwards, vacuum thoroughly.

Not recommended for:

- Herringbone parquet
- Parquet without V-grooves.

CONSUMPTION:

Depending on the sort of wood and the preparation: about 30 to 50 g/m².

These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.

TECHNICAL CHARACTERISTICS:

Physical resistance at 20°C: fl uid

Colors: white, light-grey, dark grey, extra dark.

Density [kg/m³]: White d =1.09(+0.01)

Light grey d =1.10(+0.01)

Dark grey d =1.10(+0.01)

Extra dark d =1.00(+0.01)

Viscosity: 340cP(+40) 58KU(+5)

Solubility in water: 100 %

Flash point [°C]: not inflammable.

STORAGE:

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging. Do not allow to freeze.

PACKAGING:

2,5 liter cans, 100 ml bottles.

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.

Date TDS: 16/08/12

MUYLLE FACON

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.

Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)

Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823

info@muyllefacon.be - www.rubiomonocoat.com

