

# Rubiomonocoat SIDING OIL

## 0% VOC!

### DESCRIPTION

**Rubio Monocoat Siding Oil** is a hardwax oil specially developed for the colouring and protecting of exterior, vertical wood surfaces (sidings, windows, doors, fences...).

*This product is part of the RMC Siding Oil Duo System:*

RMC Siding Oil Duo System – a durable treatment in 3 steps:

1. Preparation
2. UV protection: RMC Sunprimer Color
3. Applying oil: RMC Siding Oil

**Rubio Monocoat Siding Oil** is applied in one coat. The molecular binding with the wood fibres ensures long-lasting protection while retaining the natural appearance of the wood. Available in a wide range of standard colours.

### DIRECTIONS FOR USE

1. Remove varnish or other products - that are not from the **Rubio Monocoat** range - until the bare wood is reached.
2. Rinse the surface with **RMC Exterior Wood Cleaner** (consult the technical data sheet).
3. Rinse with clear water. Allow to dry.
4. Apply **Rubio Monocoat Sunprimer Color** (consult the technical data sheet).
5. Allow the surface to dry once more. Immediately apply the **Rubio Monocoat Siding Oil** using a sprayer, brush, roller, cloth or sponge. Allow to soak in for 5 to 10 minutes. Wipe off any excess product working along the length of the wood.

The materials used can be cleaned with **RMC Biocleaner**.

### TECHNICAL SPECIFICATIONS:

Basis: mixture of natural oils and hardwaxes.

Consistency: liquid.

Colour: extensive range of colours.

Flash point: cc (astm d93): > 102°C (Pensky Martens)

Density: Pure: 0.93 g/cm<sup>3</sup> - colours: from 1 to 1.4 g/cm<sup>3</sup>

VOC: 0 g/l (2004/42/CE, 1999/13/CE)

### DRYING TIME:

Weather resistant after 12 hours. Protect the surface from rain during the drying period.

- Protects and colours your wood in one coat.
- Molecular binding with the wood
- Exceptional protection from UV and mold (in combination with RMC Sunprimer Color)
- Natural finish
- Good protection against weathering
- Easy to maintain without needing to sand
- Allows wood to breathe and repels water
- Does not flake off
- Does not contain water
- 0% VOC

### USAGE:

Depending on the type of wood and gradient of the cabin: 30 to 50 m<sup>2</sup>/l.

*These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.*

### MAINTENANCE:

In order to keep the wood in optimal condition later on, it is sufficient to perform a maintenance with the RMC Siding Oil. This maintenance is easy to perform.

### PACKAGING:

1l – 2,5 l – 5 l can.

### STORAGE:

The product can be stored for up to 12 months in a dry place and in the original packaging.

### CAUTION:

**Under no circumstances may the product be diluted! Cloths, which have been permeated with oil, can ignite spontaneously. They should be submerged in water after use!**

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety data sheet before application. Date TDS: 1/04/2011

**MUYLLE FACON**

**MADE IN BELGIUM** by N.V. MUYLLE - FACON S.A.  
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)  
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823  
info@muyllefacon.be - [www.rubiomonocoat.com](http://www.rubiomonocoat.com)

